

High and Standard Definition SDI, Analog and Audio Signal Monitor



The LCDSCOPE HDWVA has been designed to satisfy specific requirements requested by cost conscious users who need high quality, accuracy Multi Genned with familiar and intuitive operation.

The LCDSCOPE series has no cathode ray tube, using instead a liquid crystal display. It therefore has none of the problems associated with CRT's such as focus, stigmatism, parallax, EHT failure or high maintenance costs.

The LCDSCOPE contains the latest proprietary, digital designs from Hamlet, producing a range of unique PAL and NTSC devices, which may be used in a variety of environments. The LCDSCOPE makes an ideal replacement for existing or failing CRT units but is itself only 160mm deep. Like other innovative and award winning Hamlet products, the LCDSCOPE establishes a new method of measurement and monitoring utilising a base unit with two options, both of which may be retro fitted. As with all Hamlet products the LCDSCOPE includes a host of features and functions normally only associated with much more expensive devices.

This product contains proprietary designs.

Features and Functions

- HD SDI, SD SDI, Composite, component, - plus 4 audio bar graphs and phase display
- Multi-standard NTSC & PAL
- Built-in low maintenance LCD
- Full measurement functionality including, full field line select
- Gamut violation display and alarm
- External ref.
- HFT™ hands free timing.
- On screen mode displays
- Audio Stereo ¼" Prof jack socket
- RS232 remote control
- Powered via 12Vdc mains adapter or from in-built batteries
- Only 160mm deep, rack mount, stand alone or portable operation
- Weighs only 2.5Kg

Standards supported

1920 x 1080/60/2:1 1920 I 74.25MHz.
1920 x 1080/59.94/2:1 1920 I 74.25MHz/1001
1920 x 1080/50/2:1 1920 I 74.25MHz
1920 x 1080/30/1:1 1920 P 74.25MHz
1920 x 1080/29.97/1:1 1920 P 74.25MHz/1001
1920 x 1080/25/1:1 1920 P 74.25MHz
1920 x 1080/24/1:1 1920 P 74.25MHz
1920 x 1080/23.98/1:1 1920 P 74.25MHz/1001
1920 x 1080/30 (sf) 1920 Seg Form 74.25MHz
1920 x 1080/29.97 (sf) 1920 SF
74.25MHz/1001
1920 x 1080/25 (sf) 1920 SF 74.25MHz
1920 x 1080/24 (sf) 1920 SF 74.25MHz
1920 x 1080/23.98 (sf) 1920 SF
74.25MHz/1001
1280 x 720/60/1:1 1280 P 74.25MHz
1280 x 720/59.94/1:1 1280 P 74.25MHz/1001

TECHNICAL SPECIFICATION

INPUTS

Composite input. BNC connector with loop through output. Return loss better than 40dB. Zin of 22k. Max dc +/- 3 volts.
YC input. 4 pin mini din socket with loop through output. Return loss better than 40dB. Zin of 22k. Max dc +/- 3 volts.
Component input. 3 x BNC connectors with switchable terms. Return loss better than 40dB. Zin of 75R or 22k. Max dc +/- 3 volts. YCrCb or RGB.
HD Serial digital input. BNC connector. Input impedance 75 ohms. Max d.c. +/- 10V.
SMPTE 292 serial component. 800mV pp +/-10% auto equalised up to 300 metres of cable.
Serial digital output. BNC connector. Output impedance 75 ohms. Equalised version of the serial digital input.
External ref input. BNC connector with loop through output. Return loss better than 40dB. Zin of 22k. Max dc +/- 3 volts.

AUDIO

4 x Analog balanced inputs. Zin 22K.

AUDIO MONITORING OUTPUT

Quarter inch professional stereo jack.

REMOTE CONTROL

9 pin D socket for GPI, data up/down load and remote control

POWER

10 to 13V d.c. to 2.1mm jack. 1A max.

ENVIRONMENT

Indoor use, 5 to 45 deg.C. ambient to 2,000m.
Max humidity 80% to 31 deg.C decreasing to 50% at 40 deg.C.
Overvoltage category 2. Pollution degree 1.

DISPLAY AREAS

Display 100mm x 75.5mm viewing area.
Waveform 256 pixels wide x 240 pixels high.
Audio/Gamut area 64 pixels wide x 240 pixels high.

WAVEFORM MONITOR

Response Flat is +/- 0.5% 50Hz to 30MHz.
Low Pass is -3db @ 1.5MHz, -60db @ 6.75MHz.
Timebase H, 2H and Hmag (x5). V, 2V and Vmag.
Line select is any line from the frame.
Parade is a 3H display of input or filter parade.

VECTOR MONITOR

Video Traditional component or composite display.
Component accuracy 0.2%. Bandwidth 15MHz .
Composite accuracy 1%. Bandwidth 1.3MHz .
Audio Stereo phase display of left or right audio pair. Phase accuracy 2 deg.
Gamut Poly™ display of RGB signal shows up illegal colours.

AUDIO MONITOR

Accuracy Better than 0.1db over full scale range.
Characteristics BBC, EBU, Nordic and VU.

PHYSICAL

DIMENSIONS :- 21.4 x 13.1 x 18.5cm

WEIGHT :- 2.5Kg

WARRANTY:- 1 Year

Extendable free on registration:- To 2 Years
By using the service area of our Website
<http://www.hamlet.co.uk/serv.html>

ORDERING INFORMATION

HDWVA LCDSCOPE

In-Built LCD display, compact CRT replacement technology With all options included provides analog composite, component, HD SDI, SD SDI and audio monitoring capability

OPTIONS

292 - SRM	Single Rack Mount Kit
292 - DRM	Dual Rack Mount Kit
292 - AMU	Audio monitoring accessory
292 - SCC	Soft carry case

Specifications and features herein are subject to change without prior notice. Hamlet Video International Limited products are covered by a number of Applied or Granted UK, North American and World Patents. Prior art is claimed in All Territories on features and functions incorporated in the product designs herein. Hamlet is a registered Trademark of Hamlet Video International Limited. Flexiscope, Whichwire and Videoscope are registered Trademarks of Hamlet Video International Limited. Monitor Scope, Digi Scope, Adept, LCDSCOPE, Protean, Digi Gen, VidScope, GenPen, Micro Scope, Pico Scope, PC Scope, Chameleon, Digital Window, Programme Level Meter and Stereo Scope are Trade Marks of Hamlet Video International Limited. Copyright © 2004 Hamlet Video International

Hamlet products are Manufactured to ISO9001.2000 and ISO14001 specification
Our most up to date information is available on our Website

03/05

Hamlet Video International Ltd Maple House, 11 Corinium Business Centre, Raans Road, Amersham, Bucks, HP6 6FB, UK
Tel:- +44 (0)1494 729728 Fax:- +44 (0)1494 723 237 Freephone (UK) 0500 625525
E-mail: sales@hamlet.co.uk Website: www.hamlet.co.uk

Hamlet Video International USA, Tecads Inc, 23 Del Padre St, Foothill Ranch, CA 92610, U.S.A.
Tel: +1 (949) 597 1053, Toll Free: (866) 4 HAMLET, Fax: +1 (949) 597 1094
E-mail: sales@hamlet.us.com Website: www.hamlet.us.com

HAMLET®
EXCELLENCE IN VISION