



Multiformat Rackmountable ½ rack, 1RU, Waveform, Vector & Audio Monitor & Generator rasterizer*



The DigiScope DS900 is unique; a multiple input, low power, 1RU mountable, measurement and monitoring multi-viewer of all 3G, I component and composite video signals with embedded, AES/E analogue audio, with test signal generation and EYE display ca With outputs to any DVI or XVGA monitor the DS900 is ideal fo any broadcast measuring or monitoring environment.

Each multi-view display quadrant can display a tiled T&M display input being investigated with waveforms, vectorscope and r audio displays. The capability and the flexibility of choice of utilis four inputs with modules of your choice is uncommon in an instr of this size.

Ideal for master control, pre or post production monitoring, due to its size the DS900 is also ideal for Mobile production units, trolleys, uplinks, OB vehicles. Indeed anywhere serial digital signals or multi-format measurement and monitoring are required.

The modular nature of the DigiScope DS900 instrument ensures it's easy for the user to upgrade at any time, as required. The potential to choose what you need when you want it, with the fulfilment and capability not seen before the DS900 provides an excellent return on investment.

This product contains proprietary patented designs.

A Hamlet "Made to Measure product"

Features and Functions

- World's first 4 input, multi-format, 1/2 rack, 1U, measurement and monitoring multi-viewer with touch screen control.
- 3G, HD, SD, Component, Composite video signals with embedded, AES/EBU and Analog audio supported.
- Four input module slots, accepts all series 900 modules
- Unique four-way multi-view measurement displays of inputs
- Display 4 inputs simultaneously, each with its own tiled T&M display of your choice
- Mix and match modules as required, including test signal generation and EYE
- Easy access to full waveform and vectorscope functionality
- Video output via DVI, XVGA and Audio I/O and jack for headphones
- Data and gamut analysis, with time code logging of assigned errors
- 12 Vdc powered via XLR mains adapter or external batteries or camera supply

Module Options Available Description

- 3G, HD, SD Video input module
- 3G, HD, SD Video input module with EYE pattern included
- Video Generator
- Audio

** Depending on installed Module see separate module datasheets for more information*

See our website for applications

www.hamlet.co.uk

TECHNICAL SPECIFICATION

The DigiScope 900 has four series 900 module input slots - feature sets are dependant on the module selected.

OUTPUTS

Serial digital output
BNC connector. Output impedance 75 ohms. SMPTE 292, SMPTE 259M, ITU-R BT.601/656 serial component. 800mV pp.

WAVEFORM MONITOR

Response Flat is +/- 0.5% 50Hz to 5.5MHz. Low Pass is -3db @ 1.5MHz, -60db @ 6.75MHz. Timebase H, 2H and Hmag (x5). V, 2V and Vmag. Line select is any line from the frame. Parade is a 3H display of input or filter parade

VECTOR MONITOR

Video Traditional component or composite display. Component accuracy 0.2%. Bandwidth 3.375MHz. Composite accuracy 1%. Bandwidth 1.3MHz.

AUDIO MONITOR

Audio Stereo phase display of left or right audio pair. Phase accuracy 2 deg. Accuracy Better than 0.1db over full scale range. Characteristics BBC, EBU, Digital, DIN, Nordic and VU.

AUDIO MONITORING OUTPUT

D connector and 3.5mm stereo jack.

OUTPUTS

Video
output to DVI or XVGA monitor, (1024 x 768 @ 60Hz digital or analogue monitor, via a DVI-I socket)
Audio
output to D connector and 3.5mm jack

REMOTE CONTROL

ETHERNET (RJ45) or USB

POWER

10 to 13V d.c. to 4 pin XLR socket. 3A max.

ENVIRONMENT

Indoor and Out door use, 5 to 45 deg.C. Ambient to 2,000m. Max humidity 80% to 31 deg.C decreasing to 50% at 40 deg.C. Overvoltage category 2. Pollution degree 1.

PHYSICAL

DIMENSIONS: - 20.5 x 32 x 4.3 cm.

WEIGHT: - 1.5Kg.

WARRANTY: - Upon registration - 4 years from purchase date.

By using the AbsoluteCare registration area of our web site, otherwise 1 year.

<http://www.hamlet.co.uk/support/warranty/>


ORDERING INFORMATION

DS9000 DIGISCOPE

At least one module is required, there are four modules to choose from:

OPTIONS series 900 Modules

3G, HD, SD Video input module
3G, HD, SD Video input module
with EYE pattern included
Video Generator
Audio



Specifications and features herein are subject to change without prior notice. Hamlet Video International Limited products are covered by a number of Applied or Granted UK, North American and World Patents. Prior art is claimed in All Territories on features and functions incorporated in the product designs herein. Hamlet is a registered Trademark of Hamlet Video International Limited. Flexiscope, Whichwire and Videoscope are registered Trademarks of Hamlet Video International Limited. Monitor Scope, Digi Scope, Adept, LCD Scope, Protean, Digi Gen, VidScope, AudioChex, GenPen, Micro Scope, Pico Scope, PC Scope, Chameleon, Digital Window, Programme Level Meter and Stereo Scope are Trade Marks of Hamlet Video International Limited.

Hamlet products are Manufactured to ISO9001.2000 and ISO14001 specification.

Our most up to date information is available on our web site.

Copyright © 2012 Hamlet Video International
18/07/2012

Hamlet Video International Ltd, Maple House, 11 Corinium Business Centre, Raans Road, Amersham, Bucks, HP6 6FB, England. Tel: - +44 (0) 1494 729 728 Fax: - +44 (0) 1494 723 237
Freephone (UK): - 0500 625525 E-mail: sales@hamlet.co.uk Website: www.hamlet.co.uk

HAMLET[®]
EXCELLENCE IN VISION

USA Master Distribution, Omnivue New York, NY 10016 USA
Tel: - +866-4-HAMLET or 001 212 779 2580 Website: www.hamlet.tn